



SELEX GALILEO

A Finmeccanica Company



NSU - NAVIGATION SENSOR UNIT

The NSU is a compact lightweight Integrated Navigation System.

The unit includes an Inertial Measurement Unit (IMU), a Navigation Computer, an embedded airborne C/A-code GPS Receiver, DGPS, static and dynamic pressure sensors.

The main task of the equipment is to provide changes in aircraft rate, attitude, magnetic heading, position, altitude and airspeed for use by the flight control system, autonomous navigation system and other sensors (e.g.: Radar Antenna stabilization).

The NSU provides:

- Navigation mode with the utilization of GPS, IMU, Air Data Sensor, Magnetic heading reference;
- AHRS mode with the utilization of IMU, Air Data Sensor, Magnetic heading reference;
- ADS mode with the utilization of Air Data Sensors, Temperature sensor and baro altitude correction data;
- Built-in Test and monitoring capability for failure detection and management;
- System Pre-Flight test and initialization interface.

APPLICATIONS:

- Unmanned Air Vehicles.
- Target drones.
- Surveillance systems.
- Optronic system stabilization and targeting.
- Aircraft instrumentation pods.
- SAR antenna stabilization.
- Fixed & rotary wings aircraft, where a navigation sensor is required.

NSU - Navigation Sensor Unit

FEATURES

- Compact, lightweight, small size unit
- Excellent cost/performance ratio
- Multiple communication channels (RS-422 and Ethernet LAN, ARINC429 and Mil-STD 1553B option).

Navigation data provided by the NSU include:

- Body axis rates (p, q and r);
- Body axis accelerations (Ax, Ay and Az);
- Attitude data (roll and pitch angle);
- True Heading;
- Position (UTM zone and East North);
- Velocities (Vn, Ve and Vv);
- Altitude (Integrated inertial/aided sensor)
- Pressure altitude; Pressure altitude rate;
- True airspeed;
- Indicated airspeed;
- Static and differential pressure (Ps and Pd);
- GPS one pulse per second time mark; GPS time;
- Wind Velocity east-north;
- GPS data (X, Y, Z, satellite number, S/N, FOM, ecc)
- Total Air temperature (TAT)

The position coordinates (X,Y,Z) are referred to WGS 84 ellipsoid.



TECHNICAL CHARACTERISTICS

System Performances:

Roll&Pitch	0,2° (1σ)
Heading	0,5° (1σ)
Position	15m CEP GPS C/A Code
Velocity	0.1m/s (1σ) GPS C/A Code
Altitude	25m (1σ) GPS C/A Code
Pressure altitude	20m (1σ) (0 ÷ 11000 m) ≤ 0.34 % (>11000 m)
Indicated airspeed	1m/s (1σ)
True airspeed	1m/s (1σ) (assuming < 1°C TAT accuracy and airspeed >15m/s up to 0.95M);

Technical data

Weight:	2,6 Kg
Dimensions (LxWxH):	158x147x127 mm
Voltage supply:	28V (D0-160C) -17 to 32 Vdc (normal operation)
Power consumption:	28 W (Start-up 56W).

Environmental Characteristics:

Operating temperature range:	- 40 °C - + 70 °C
Linear Acceleration:	15 G test level for every axis and directions.
Shock:	20 g for 11 ms
Vibration:	MIL-STD-810E (jet aircraft), 20÷2000 Hz, Wo = 0,04 G²/Hz, operational.

For more information please email sales.marketing@selexgalileo.com

SELEX Galileo S.p.A. - A Finmeccanica Company

Via A. Einstein, 35 - 50013 Campi Bisenzio (FI) - Italy

This publication is issued to provide outline information only and is supplied without liability for errors or omissions. No part of it may be reproduced or used unless authorized in writing.

We reserve the right to modify or revise all or part of this document without notice.

2010 © Copyright SELEX Galileo.

www.selexgalileo.com

SELEXGALILEO\IT\Dsh-177\0110